

Instruction Manual | Bedienungsanleitung | Manual de instrucciones | Manuale d'istruzioni | Manuel d'instructions |
Handleiding | Návod k použití





P

I

U

Ta



| FPL73400v1-ex | 24W | 650mA | 34VDC | -30°C~+40°C | 595 | 595 | 27 | IP20 | IP40 |
|---------------|-----|-------|-------|-------------|-----|-----|----|------|------|
| FPL73400v1-ex | 28W | 750mA | 34VDC | -30°C~+40°C | 595 | 595 | 27 | IP20 | IP40 |
| FPL73400v1-ex | 32W | 850mA | 34VDC | -30°C~+40°C | 595 | 595 | 27 | IP20 | IP40 |
| FPL73400v1-ex | 36W | 950mA | 34VDC | -30°C~+40°C | 595 | 595 | 27 | IP20 | IP40 |



I

U

λ

I

U

Ta

Tc



| DRIVER | Input | | | Output | | Ta Tc | | | |
|-------------------|------------|-------------------|------|----------------------------------|----------|-------------|-------|-----|---------------|
| LD230036/mc-C0950 | Max. 250mA | 220-240V~ 50/60Hz | >0.9 | 950mA 850mA 750mA 650mA | 30-42VDC | -30°C~+40°C | +80°C | N/A | FPL73400v1-ex |

OFF ↔ ON



| PIN1 | PIN2 | I _{out} (mA) |
|------|------|-----------------------|
| OFF | OFF | 650 |
| ON | OFF | 750 |
| OFF | ON | 850 |
| ON | ON | 950 |

ACCESSORIES



| | | |
|--------|--|-------------------|
| LA6039 | Loop through adaptor for LD230036/mc-C0950 | LD230036/mc-C0950 |
|--------|--|-------------------|